

FLAT DOT MATTE

(ZSO560)

GENERAL PROPERTIES

- Digital printing PVC media that has designed to remove bubbles with high performance
- Only dry application with dot adhesive technology
- Can be repositioned initially, but the adhesive is stronger after being positioned.
- Work with all popular solvent, Latex and UV curable inkjet printers.
- Dot adhesive technology, Permanent adhesive, Matte surface PVC Calender.

* Condition / Setting / Caution

- When printing, please print out having some unprinted space.
- When installing, please have enough drying time, after printing. (Drying times for 1 day is recommended.)
- Recommended to use double-sided tape to prevent detachment after installation.
- Due to PVC shrinking, it is recommended for the printing surface to be laminated.
- Once mounted on the PVC surface, it may leave behind an adhesive residue if removed.
- Removing the film while the surface is still hot is not recommended (eg. shop windows, metal surfaces, etc.). Otherwise, the adhesive may completely stay on the surface. Please allow the surface to cool prior to removal of the film.

* Adhesive strength

Initial 20 min. ≥ 700 g/inch
Middle 1 day ≥ 900 g/inch
Final 3 days ≥ 1,100 g/inch

* Application surface


- Indoor & outdoor Advertising, Windows, Acrylic
Flat or compound/curved surfaces, rivets, etc.,

* Non-applicable surface

- Right-angle side, weak painted wall, embossed surface, etc.

* Warranty : 6 months (1 year durability)

Specifications

Length (ft)	164	Width (inch)	54 / 60
Weight (gsm)	135	Total Weight (gsm)	280
Caliper (mil)	4.9	Total Caliper (mil)	11
Inner Core (inch)	3	Coating	Resin
Surface	Matte	Base Material	PVC
		Printer	

KEY FEATURES

- Dot adhesive technology
- Permanent adhesive (Initially repositionable)
- Easy to install
- Bubbles free and only dry application

Application

- Architectural window decorations, Glass and Plastic flatness, Window graphics, Labels and decals, Retail aisle banners

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature (Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.