

ECO-SOL CLEAR BACKLIT 200 GLOSSY


(SO800W)

Details

- Optically Clear Polyester film for eco-solvent, solvent, latex and UV curable inks.
- High ink density, vivid colors with high gloss and outstanding image resolution with or without light
- Scratch resistant and waterproof with advanced coating. No need for secondary process.
- Rigid substrate for stay flat and curl-free
- Excellent material for white acrylic backlit plate
- Certified for HP Latex Inks

Certified for
HP Latex Inks

Specifications

| | | | |
|-------------------|-------|---------------|---|
| Length (ft) | 100 | Width (inch) | 54"/60" |
| Weight (gsm) | 285 | Coating | Resin |
| Caliper (mil) | 8.2 | Base Material | PET |
| Inner Core (inch) | 3 | Inks |  |
| Surface | Clear | | |

KEY FEATURES

- Optically Clear PET
- High Ink Load
- Eco-sol, Latex & UV printable
- Excellent Rigidity (8.2 mil)
- Scratch-Resistant & Curl-free

Application

- Light box graphic, Backlit trade show display, Luminous advertising, Department store display, Bus Shelter & Metro illuminated signage
- For White Acrylic Backlit Plate

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.