

FLAT DOT Clear PET

(ZSO520)

Details

- Dot adhesive technology, Permanent adhesive, Clear Polyester film.
- Designed to remove bubbles with high performance: Air Egress
- Repositioning available initially, but the adhesive be stronger after positioned.
- Can be installed by anyone without special techniques because of the dot technology.
- Eco-solvent, Solvent, UV, Latex ink compatibility


* Condition / Setting

Highly recommend to test this sample roll before you try to target

Recommended for indoor usage

Clean the mounting object before applying this film

Specifications

Standard length (ft)	100	Width (inch)	54"
Total weight (g/ m²)	220	Coating	Clear
Base weight (g/ m²)	105	Base Material	PET
Total caliper (mil)	7	Inks	
Base caliper (mil)	3	Peel Strength (SUS, gf/25mm)	Initial 20 min. ≥ 50
Inner Core (inch)	3		24 hours ≥ 100

KEY FEATURES

- Dot adhesive technology
- Permanent PSA
- Optically clear Polyester film
- Easy to install
- Bubbles free

Application

- Architectural window decorations, Glass and Plastic flatness, Window graphics, Trade Show

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : 6 month after opening the box (1 year durability)

* Cautions

- Recommended to put the blank space when printing the products
- For outdoor use, recommended to use outdoor lamination film to prevent discoloration.
- Recommended to use the products after complete or enough drying time
- Recommended to use double-sided tape or proper finish to prevent detachment from the substrate.

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.