

FLAT DOT PP

(ZSO590)

Details

- Dot adhesive technology, Permanent adhesive, Eco-friendly with PVC-free base film
- Designed to remove bubbles with high performance without using special liquid mixture.
- Repositioning available initially, but the adhesive be stronger after positioned.
- Installed by anyone without special techniques because of the dot technology.
- Eco-solvent, Solvent, UV, Latex ink compatibility

* Condition / Setting


Highly recommend to test this sample roll before you try to target

Recommended for indoor usage

For outdoor use, recommended to use outdoor lamination film to prevent discoloration

Clean a mounting object before applying this film

Specifications

Standard length (ft)	50m	Width (inch)	54"
Total weight (g/ m ²)	275	Coating	Resin
Caliper (mil)	10.4 total (6.4 / 0.8 / 3.2)	Base Material	PP
		Inks	
Surface	Matte	Peel Strength (SUS, gf/25mm) ASTM D903(180°)	20 min : 1000 ≥
Inner Core (inch)	3		24hr : 1500 ≥

KEY FEATURES

- Dot adhesive technology
- Permanent adhesive
- PVC-free (Polypropylene)
- Easy to install
- Bubbles free (air-egress)
- Minimize the curling printed by Latex

Application

- Architectural window decorations, Glass and Plastic flatness, Window graphics, Trade Show

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature

* Cautions

- Recommended to put blank space on edges when printing
- Recommended to use the products after complete or enough drying time
- Recommended to use double-sided tape or proper finish to prevent detachment from the substrate.

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

www.naturamedia.us

1750 Lakes Pkwy, Lawrenceville, GA 30043

TEL 470-359-2111
FAX 470-359-2199