

## DURATIN SYNTH ROLL UP BANNER


(ES500)

### Details

- Unique scratch-resistant coating eliminates the need for lamination
- Excellent blockout and Curl-free
- Great option for long-term or high use rollup banner and tradeshow panels.
- Double layer coating on PP base, providing anti-curl properties.
- Satin finish reduces glare, and improves color density
- Certified for HP Latex Inks

Certified for  
HP Latex Inks

### Specifications

|                   |       |               |   |
|-------------------|-------|---------------|---|
| Length (ft)       | 100   | Width (inch)  | 36"/50"   |
| Weight (gsm)      | 165   | Coating       | Resin   |
| Caliper (mil)     | 8.7   | Base Material | Poly propylene  |
| Inner Core (inch) | 3     | Inks          |  |
| Surface           | SATIN |               |   |

### KEY FEATURES

- Proprietary Scratch-Resistant Coated
- No lamination needed
- Excellent Blockout
- Curl-Free Properties
- Durable for Outdoor Use

### Application

- Rollup Stands, Trade Show Panels, Indoor/Outdoor POS, Retail Aisle Banners

### General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional.
- Storage : Recommended to store in closed original packaging in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.  
(Humidity 35~65% RH)
- Shelf Life : One year stored in original packaging at recommended temperature.  
(Coating warranty guaranteed for 6 months from date of purchase)

### How to buy :

- Please call 1-470-359-2111 to place an order or visit [www.naturamedia.us](http://www.naturamedia.us) for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied. All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.