


Floor Graphic Wall Deco Film

(ZFG500)

Details

Total Solution for Digital Printing & Floor Graphic & Wall Graphic Application
 Provide excellent scratch-resistant , print image
 Don't require an additional protective laminate
 Generates excellent removability and slip-resistant
 Can be applied on various surfaces including carpet and rough surfaces

Specifications

Length (m)	75	Width (inch)	48" / 54"
Weight (g/ m ²)	450	Base Material	PVC + FABRIC
Caliper (um)	15	Inks	
Liner weight (g/ m ²)	80 ± 10	Shrinkage (mm)	Less than 0.5
Peel Adhesion (24hrs) gf/25mm	500 ± 200		
180° Peel (gf/inch) adhesion on SUS304	6~7N/25mm	(size : 1inch×150mm condition : 23 °C 65%RH×24h)	

KEY FEATURES

Multi-purpose Film for Wall & Floor
 Excellent Removability
 R12 slip-resistance certified (DIN-51130 by IFA)
 Scratch-resistant
 No extra lamination required

Application

Tradeshow (Carpet , Wall & Floor Graphic), POP (Wall & Floor Graphic), Sidewalk Graphic

Durability

- In/out door floor up to 3 months (depending on traffic)
- Indoor wall up to 24 months
- Outdoor wall up to 3 months

This information is provided for your reference only.
 Product's durability is depends on customer's usage of the surface where it would applied.

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment. (Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
 All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.